



## Appendix F for BT LE Test Data

**Product Name:** Tablet

**Test Model:** TAB 50

### Environmental Conditions

Temperature:	22.3° C
Relative Humidity:	52.8%
ATM Pressure:	100.0 kPa
Test Engineer:	Nick Peng
Supervised by:	Ling Zhu





## F.1 RF Output Power

Condition	Mode	Frequency (MHz)	Max EIRP (dBm)	Limit (dBm)	Verdict
NVNT	BLE	2402	0.48	20	Pass
NVNT	BLE	2440	0.43	20	Pass
NVNT	BLE	2480	0.32	20	Pass

Condition	Mode	Frequency (MHz)	Max EIRP (dBm)	Limit (dBm)	Verdict
NVLT	BLE	2402	0.46	20	Pass
NVLT	BLE	2440	0.42	20	Pass
NVLT	BLE	2480	0.31	20	Pass

Condition	Mode	Frequency (MHz)	Max EIRP (dBm)	Limit (dBm)	Verdict
NVHT	BLE	2402	0.44	20	Pass
NVHT	BLE	2440	0.40	20	Pass
NVHT	BLE	2480	0.30	20	Pass

\*\*\*Note: 20 bursts had been captured for power measurement.







## F.2 Power Spectral Density

Condition	Mode	Frequency (MHz)	Max PSD (dBm/MHz)	Limit (dBm/MHz)	Verdict
NVNT	BLE	2402	0.4	10	Pass
NVNT	BLE	2440	0.35	10	Pass
NVNT	BLE	2480	0.24	10	Pass

PSD NVNT BLE 2402MHz




PSD NVNT BLE 2440MHz





## PSD NVNT BLE 2480MHz






### F.3 Occupied Channel Bandwidth


Condition	Mode	Frequency (MHz)	Center Frequency (MHz)	OBW (MHz)	Lower Edge (MHz)	Upper Edge (MHz)	Limit OBW (MHz)	Verdict
NVNT	BLE	2402	2402.008	1.056	2401.48	2402.536	2400 - 2483.5MHz	Pass
NVNT	BLE	2440	2440.007	1.055	2439.479	2440.535	2400 - 2483.5MHz	Pass
NVNT	BLE	2480	2480.007	1.055	2479.479	2480.535	2400 - 2483.5MHz	Pass

OBW NVNT BLE 2402MHz






## OBW NVNT BLE 2440MHz



## OBW NVNT BLE 2480MHz






## F.4 Transmitter unwanted emissions in the out-of-band domain


Condition	Mode	Frequency (MHz)	OOB Frequency (MHz)	Level (dBm/MHz)	Limit (dBm/MHz)	Verdict
NVNT	BLE	2402	2399.5	-60.78	-10	Pass
NVNT	BLE	2402	2399.444	-64.53	-10	Pass
NVNT	BLE	2402	2398.444	-71.54	-20	Pass
NVNT	BLE	2402	2398.388	-70.95	-20	Pass
NVNT	BLE	2480	2484	-71.61	-10	Pass
NVNT	BLE	2480	2484.055	-69.99	-10	Pass
NVNT	BLE	2480	2485.055	-70.7	-20	Pass
NVNT	BLE	2480	2485.11	-72.66	-20	Pass

Tx. Emissions OOB NVNT BLE 2402MHz





## Tx. Emissions OOB NVNT BLE 2480MHz







## F.5 Transmitter unwanted emissions in the spurious domain


Condition	Mode	Frequency (MHz)	Range	Spur Freq (MHz)	Spur Level (dBm)	Limit (dBm)	Verdict
-----------	------	-----------------	-------	-----------------	------------------	-------------	---------

Tx. Spurious NVNT BLE 2402MHz



Tx. Spurious NVNT BLE 2480MHz







## F.6 Receiver spurious emissions

Condition	Mode	Frequency (MHz)	Range	Spur Freq (MHz)	Spur Level (dBm)	Limit (dBm)	Verdict
-----------	------	-----------------	-------	-----------------	------------------	-------------	---------

Rx. Spurious NVNT BLE 2402MHz



Rx. Spurious NVNT BLE 2480MHz





## F.7 Receiver Blocking

Test Mode	Test Channel (MHz)	Wanted Signal Mean Power from Companion Device (dBm)	Blocking Signal Frequency (MHz)	Blocking Signal Power (dBm)		Type of Blocking Signal	PER(%)		Test Result
				Test Value	Limit		Test Value	Limit	
BLE	2402	-69	2380	-27	≥-34	CW	1.44	10	Pass
			2504	-21	≥-34	CW	2.62	10	Pass
			2300	-25	≥-34	CW	1.34	10	Pass
			2584	-23	≥-34	CW	1.30	10	Pass
	2480	-69	2380	-30	≥-34	CW	1.55	10	Pass
			2504	-25	≥-34	CW	3.10	10	Pass
			2300	-28	≥-34	CW	2.47	10	Pass
			2584	-20	≥-34	CW	1.02	10	Pass

