



# **RADIO TEST REPORT**

## **ETSI EN 300 328 V2.2.2 (2019-07)**

**Product :** Tablet

**Trade Mark :** CUBOT

**Model Name :** TAB KINGKONG MINI

**Family Model :** N/A

**Report No. :** S25052400907001

### **Prepared for**

Shenzhen Huafurui Technology Co., Ltd.

Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993 Jiaxian Road,  
Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, P.R. China

### **Prepared by**

Shenzhen NTEK Testing Technology Co., Ltd.

No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen,  
Guangdong, People's Republic of China

Tel. 0755-23200050 Website: <http://www.ntek.org.cn>

**TEST RESULT CERTIFICATION**

**Applicant's name** ..... : Shenzhen Huafurui Technology Co., Ltd.  
**Address** ..... : Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993 Jiaxian Road, Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, P.R. China  
**Manufacturer's Name** ..... : Shenzhen Huafurui Technology Co., Ltd.  
**Address** ..... : Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993 Jiaxian Road, Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, P.R. China

**Product description**

**Product name** ..... : Tablet  
**Trademark** ..... : CUBOT  
**Model Name** ..... : TAB KINGKONG MINI  
**Family Model** ..... : N/A

**Standards** ..... : ETSI EN 300 328 V2.2.2 (2019-07)

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the of article 3.2 of the Directive 2014/53/EU requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

**Test Sample Number** ..... S250524009006

**Date of Test** .....

**Date (s) of performance of tests** ..... May 29, 2025 ~ Jul. 01, 2025

**Date of Issue** ..... Jul. 01, 2025

**Test Result** ..... **Pass**

Prepared By : Allen Liu  
Allen Liu  
(Project Engineer)

Reviewed By : Aaron Cheng  
Aaron Cheng  
(Supervisor)

Approved By : Alex Li  
Alex Li  
(Manager)

Table of Contents	Page
1 . GENERAL INFORMATION	7
1.1 GENERAL DESCRIPTION OF EUT	7
1.2 INFORMATION ABOUT THE EUT	8
1.3 TEST CONDITIONS	13
1.4 TEST CONFIGURATION OF EUT	13
1.5 DESCRIPTION OF TEST CONDITIONS	14
1.6 DESCRIPTION OF SUPPORT UNITS	15
1.7 EQUIPMENTS LIST FOR ALL TEST ITEMS	16
2 . SUMMARY OF TEST RESULTS	17
2.1 TEST FACILITY	18
3 . RF OUTPUT POWER	19
3.1 LIMITS OF RF OUTPUT POWER	19
3.2 TEST PROCEDURE	19
3.3 DEVIATION FROM TEST STANDARD	19
3.4 TEST SETUP	19
3.5 TEST RESULTS	20
4 . ACCUMULATED TRANSMIT TIME, FREQUENCY OCCUPATION AND HOPPING SEQUENCE	21
4.1 LIMITS OF ACCUMULATED TRANSMIT TIME, FREQUENCY OCCUPATION AND HOPPING SEQUENCE	21
4.2 TEST PROCEDURE	21
4.3 DEVIATION FROM TEST STANDARD	21
4.4 TEST SETUP	22
4.5 TEST RESULTS	22
5 . OCCUPIED CHANNEL BANDWIDTH	23
5.1 LIMITS OF OCCUPIED CHANNEL BANDWIDTH	23
5.2 TEST PROCEDURE	23
5.3 DEVIATION FROM TEST STANDARD	24
5.4 TEST SETUP	24
5.5 TEST RESULTS	24
6 . TRANSMITTER UNWANTED EMISSIONS IN THE OUT-OF-BAND DOMAIN	25
6.1 LIMITS OF TRANSMITTER UNWANTED EMISSIONS IN THE OUT-OF-BAND DOMAIN	25

Table of Contents	Page
6.2 TEST PROCEDURE	25
6.3 DEVIATION FROM TEST STANDARD	26
6.4 TEST SETUP	26
6.5 TEST RESULTS	26
7 . HOPPING FREQUENCY SEPARATION	27
7.1 LIMITS OF HOPPING FREQUENCY SEPARATION	27
7.2 TEST PROCEDURE	27
7.3 DEVIATION FROM TEST STANDARD	27
7.4 TEST SETUP	28
7.5 TEST RESULTS	28
8 . TRANSMITTER UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN	29
8.1 LIMITS OF TRANSMITTER TRANSMITTER UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN	29
8.2 TEST PROCEDURE	29
8.3 DEVIATION FROM TEST STANDARD	29
8.4 TEST SETUP	30
8.5 TEST RESULTS (Radiated measurement)	31
8.6 TEST RESULTS (Conducted measurement)	32
9 . RECEIVER SPURIOUS EMISSIONS	33
9.1 LIMITS OF RECEIVER SPURIOUS RADIATION	33
9.2 TEST PROCEDURE	33
9.3 DEVIATION FROM TEST STANDARD	33
9.4 TEST SETUP	34
9.5 TEST RESULTS (Radiated measurement)	35
9.6 TEST RESULTS (Conducted measurement)	36
10. RECEIVER BLOCKING	37
10.1 PERFORMANCE CRITERIA	37
10.2 LIMITS OF RECEIVER BLOCKING	37
10.3 TEST PROCEDURE	38
10.4 DEVIATION FROM TEST STANDARD	39
10.5 TEST SETUP	39
10.6 TEST RESULTS	40
11. TEST RESULTS	43
11.1 Accumulated Transmit Time	43

<b>Table of Contents</b>	<b>Page</b>
11.2 Frequency Occupation	53
11.3 Dwell Time One Burst	63
11.4 RF Output Power	73
11.5 Hopping Frequency Separation	76
11.6 Occupied Channel Bandwidth	82
11.7 Transmitter unwanted emissions in the out-of-band domain	86
11.8 Transmitter unwanted emissions in the spurious domain	90
11.9 Receiver spurious emissions	97
11.10 Hopping Sequence	103
12. EUT TEST PHOTO	106
SPURIOUS EMISSIONS MEASUREMENT PHOTOS	106

Revision History

Report No.	Version	Description	Issued Date
S25052400907001	Rev.01	Initial issue of report	Jul. 01, 2025

## 1. GENERAL INFORMATION

## 1.1 GENERAL DESCRIPTION OF EUT

Equipment	Tablet	
Trade Mark	CUBOT	
Model Name.	TAB KINGKONG MINI	
Family Model	N/A	
Model Difference	N/A	
Product Description	The EUT is Tablet	
	Operation Frequency:	2402~2480 MHz
	Modulatin Type:	GFSK,π/4-DQPSK,8-DPSK
	Modulation Technology:	FHSS
	Adaptive/non-adaptive	Adaptive equipment
	Receiver categories	2
	Number Of Channel	79CH
	Antenna Designation:	FPC Antenna
	Antenna Gain(Peak)	-1.4 dBi
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	
Channel List	Refer to below Table	
Adapter	Adapter 1: Model:HJ-PD33W-EU Input:100-240V~50-60Hz 0.8A Output: 5V---3A 15W OR 9V---3A 27W OR 12V---2.75A 33W	
	Adapter 2: Model:TD-203G200170VF01 Input:100-240V~50-60Hz 0.6A Output: 5V---3AOR 9V---3A OR 12V---2.5A OR 15V---2A OR 20V---1.5A PPS: 3.3V-16V/2A OR 3.3V-11V/3A	
Battery	DC 3.87V, 10200mAh, 39.474Wh	
Rating	DC 3.87V from Battery or DC 5V/9V/12V from Adapter 1 or DC 5V/9V/12V/15V/20V from Adapter 2	
I/O Ports	Refer to users manual	
Hardware Version	T30D-UF-V1.2	
Software Version	CUBOT_TAB_KINGKONG_MINI_P131_V1.0	

## Note:

- For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

79 channels are provided to (GFSK,  $\pi/4$ -DQPSK, 8-DPSK)

Channel	Frequency (MHz)
00	2402
01	2403
.....	.....
.....	.....
.....	...
.....	.....
77	2479
78	2480

## 1.2 INFORMATION ABOUT THE EUT

### a) The type of modulation used by the equipment:

- ☒ FHSS  
☐ other forms of modulation

### b) In case of FHSS modulation:

- In case of non-Adaptive Frequency Hopping equipment:  
The number of Hopping Frequencies: .....
- In case of Adaptive Frequency Hopping Equipment:  
The maximum number of Hopping Frequencies: 79  
The minimum number of Hopping Frequencies: 79
- The (average) Dwell Time: 327.361ms Maximum

### c) Adaptive / non-adaptive equipment:

- ☐ non-adaptive Equipment  
☒ adaptive Equipment without the possibility to switch to a non-adaptive mode  
☐ adaptive Equipment which can also operate in a non-adaptive mode

### d) In case of adaptive equipment:

The maximum Channel Occupancy Time implemented by the equipment: .... / ..... ms

- ☒ The equipment has implemented an LBT based DAA mechanism
- In case of equipment using modulation different from FHSS:
    - ☐ The equipment is Frame Based equipment
    - ☐ The equipment is Load Based equipment
    - ☐ The equipment can switch dynamically between Frame Based and Load Based equipment
- The CCA time implemented by the equipment: ..... / ..  $\mu$ s
- ☐ The equipment has implemented a non-LBT based DAA mechanism  
☐ The equipment can operate in more than one adaptive mode



**e) In case of non-adaptive Equipment:**

The maximum RF Output Power (e.i.r.p.):

The maximum (corresponding) Duty Cycle:

Equipment with dynamic behaviour, that behaviour is described here. (e.g. the different combinations of duty cycle and corresponding power levels to be declared):

**f) The worst case operational mode for each of the following tests:**

- RF Output Power  
GFSK
- Power Spectral Density  
N/A
- Duty cycle, Tx-Sequence, Tx-gap  
N/A
- Accumulated Transmit time, Frequency Occupation & Hopping Sequence (only for FHSS equipment)  
8-DPSK
- Hopping Frequency Separation (only for FHSS equipment)  
 $\pi/4$ -DQPSK
- Medium Utilization  
N/A
- Adaptivity  
N/A
- Receiver Blocking  
GFSK
- Nominal Channel Bandwidth  
8-DPSK
- Transmitter unwanted emissions in the OOB domain  
 $\pi/4$ -DQPSK
- Transmitter unwanted emissions in the spurious domain  
8-DPSK
- Receiver spurious emissions  
GFSK

**g) The different transmit operating modes (tick all that apply):**

- ☒ Operating mode 1: Single Antenna Equipment
- ☒ Equipment with only one antenna
- ☐ Equipment with two diversity antennas but only one antenna active at any moment in time
- ☐ Smart Antenna Systems with two or more antennas, but operating in a (legacy) mode where only one antenna is used (e.g. IEEE 802.11™ [i.3] legacy mode in smart antenna systems)
- ☐ Operating mode 2: Smart Antenna Systems - Multiple Antennas without beam forming
- ☐ Single spatial stream / Standard throughput / (e.g. IEEE 802.11™ [i.3] legacy mode)
- ☐ High Throughput (> 1 spatial stream) using Nominal Channel Bandwidth 1
- ☐ High Throughput (> 1 spatial stream) using Nominal Channel Bandwidth 2

NOTE 1: Add more lines if more channel bandwidths are supported.

- ☐ Operating mode 3: Smart Antenna Systems - Multiple Antennas with beam forming
- ☐ Single spatial stream / Standard throughput (e.g. IEEE 802.11™ [i.3] legacy mode)
- ☐ High Throughput (> 1 spatial stream) using Nominal Channel Bandwidth 1
- ☐ High Throughput (> 1 spatial stream) using Nominal Channel Bandwidth 2

NOTE 2: Add more lines if more channel bandwidths are supported.

#### h) In case of Smart Antenna Systems:

- The number of Receive chains: .....
- The number of Transmit chains: .....
  - ☐ symmetrical power distribution
  - ☐ asymmetrical power distribution

In case of beam forming, the maximum (additional) beam forming gain: ..... dB

NOTE: The additional beam forming gain does not include the basic gain of a single antenna.

#### i) Operating Frequency Range(s) of the equipment:

- Operating Frequency Range 1: 2402 MHz to 2480 MHz
  - Operating Frequency Range 2: ..... MHz to ..... MHz
- NOTE: Add more lines if more Frequency Ranges are supported.

#### j) Nominal Channel Bandwidth(s):

- Nominal Channel Bandwidth 1: 1.196MHz
- Nominal Channel Bandwidth 2: ...../..... MHz

NOTE: Add more lines if more channel bandwidths are supported.

#### k) Type of Equipment (stand-alone, combined, plug-in radio device, etc.):

- ☒ Stand-alone
- ☐ Combined Equipment (Equipment where the radio part is fully integrated within another type of equipment)
- ☐ Plug-in radio device (Equipment intended for a variety of host systems)
- ☐ Other

#### l) The normal and the extreme operating conditions that apply to the equipment:

##### Normal operating conditions (if applicable):

Operating temperature: 15°C~35°C

Other (please specify if applicable): .....

##### Extreme operating conditions:

Operating temperature range: Minimum: -10°C Maximum 40°C

Other (please specify if applicable): ..... Minimum: ..... Maximum .....

Details provided are for the:

- ☒ stand-alone equipment
- ☐ combined (or host) equipment
- ☐ test jig

**m) The intended combination(s) of the radio equipment power settings and one or more antenna assemblies and their corresponding e.i.r.p. levels:**

• Antenna Type: FPC Antenna

☒ Integral Antenna (information to be provided in case of conducted measurements)

Antenna Gain: -1.4 dBi

If applicable, additional beamforming gain (excluding basic antenna gain): ...../..... dB

☐ Temporary RF connector provided

☐ No temporary RF connector provided

☐ Dedicated Antennas (equipment with antenna connector)

☐ Single power level with corresponding antenna(s)

☐ Multiple power settings and corresponding antenna(s)

Number of different Power Levels: .....

Power Level 1: ..... dBm

Power Level 2: ..... dBm

Power Level 3: ..... dBm

NOTE 1: Add more lines in case the equipment has more power levels.

NOTE 2: These power levels are conducted power levels (at antenna connector).

• For each of the Power Levels, provide the intended antenna assemblies, their corresponding gains

(G) and the resulting e.i.r.p. levels also taking into account the beamforming gain (Y) if applicable

**Power Level 1:** ..... dBm

Number of antenna assemblies provided for this power level: .....

Assembly #	Gain (dBi)	e.i.r.p. (dBm)	Part number or model name
1	-1.4	5.63	
2			
3			

NOTE 3: Add more rows in case more antenna assemblies are supported for this power level.

**Power Level 2:** ..... dBm

Number of antenna assemblies provided for this power level: .....

Assembly #	Gain (dBi)	e.i.r.p. (dBm)	Part number or model name
1			
2			
3			

NOTE 4: Add more rows in case more antenna assemblies are supported for this power level.

**Power Level 3:** ..... dBm

Number of antenna assemblies provided for this power level: .....

Assembly #	Gain (dBi)	e.i.r.p. (dBm)	Part number or model name
1			
2			
3			

NOTE 5: Add more rows in case more antenna assemblies are supported for this power level.

**n) The nominal voltages of the stand-alone radio equipment or the nominal voltages of the combined (host) equipment or test jig in case of plug-in devices:**

Details provided are for the:

- ☒ stand-alone equipment
- ☐ combined (or host) equipment
- ☐ test jig

Supply Voltage ☐ AC mains State AC voltage ..... V

☒ DC State DC voltage: DC 3.87V

In case of DC, indicate the type of power source

- ☐ Internal Power Supply
- ☒ External Power Supply or AC/DC adapter: DC 5V/9V/12V/15V/20V
- ☒ Battery: DC 3.87V
- ☐ Other: .....

**o) Describe the test modes available which can facilitate testing:**

See clause 1.4

**p) The equipment type (e.g. Bluetooth®, IEEE 802.11™ [i.3], IEEE 802.15.4™ [i.4], proprietary, etc.):**

Bluetooth®

**q) If applicable, the statistical analysis referred to in clause 5.4.1 q)**

(to be provided as separate attachment)

**r) If applicable, the statistical analysis referred to in clause 5.4.1 r)**

(to be provided as separate attachment)

**s) Geo-location capability supported by the equipment:**

- ☐ Yes
- ☐ The geographical location determined by the equipment as defined in clause 4.3.1.13.2 or clause 4.3.2.12.2 is not accessible to the user
- ☒ No

**t) Describe the minimum performance criteria that apply to the equipment (see clause 4.3.1.12.3 or clause 4.3.2.11.3):**

GFSK (CH00) =0.96

## 1.3 TEST CONDITIONS

	Normal Test Conditions	Extreme Test Conditions
Temperature	15°C - 35°C	-10°C ~ 40°C Note: (1)
Relative Humidity	20% - 75%	N/A
Supply Voltage	DC 3.87V	/

Note:

- (1) The HT 40°C and LT -10°C was declared by manufacturer, The EUT couldn't be operate normally with higher or lower temperature.
- (2) The measurements are performed at the highest, middle, lowest available channels.

## 1.4 TEST CONFIGURATION OF EUT

Modulation Used For Conformance Testing		
Bluetooth mode	Data rate	Modulation type
BR	1Mbps	GFSK
EDR	2Mbps	$\pi/4$ -DQPSK
EDR	3Mbps	8-DPSK

Test Channel Frequencies Configuration		
Test Channel	EUT Channel	Test Frequency (MHz)
Lowest	CH00	2402
Middle	CH39	2441
Highest	CH78	2480

## 1.5 DESCRIPTION OF TEST CONDITIONS

E-1  
EUT

## 1.6 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
E-1	Tablet	TAB KINGKONG MINI	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

## Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

## 1.7 EQUIPMENTS LIST FOR ALL TEST ITEMS

EQUIPMENT TYPE	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
EMI Test Receiver	R&S	ESPI7	101318	2025.04.17	2026.04.16	1 year
Bilog Antenna	TESEQ	CBL6111D	31216	2025.04.17	2026.04.16	1 year
Turn Table	EM	SC100_1	60531	N/A	N/A	N/A
Antnna Mast	EM	SC100	N/A	N/A	N/A	N/A
Horn Antenna	EM	EM-AH-10180	2011071402	2024.05.12	2027.05.11	3 year
Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2024.05.12	2027.05.11	3 year
Test Cable (30MHz-1GHz)	N/A	R-01	N/A	2023.06.17	2026.06.16	3 year
Test Cable (1-18GHz)	N/A	R-02	N/A	2023.06.17	2026.06.16	3 year
50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2024.04.26	2027.04.25	3 year
Pre-Amplifier	EMC	EMC051835SE	980246	2025.04.17	2026.04.16	1 year
Spectrum Analyzer	Agilent	E4440A	MY41000130	2025.04.17	2026.04.16	1 year
Filter	TRILTHIC	2400MHz	29	2024.04.26	2027.04.25	3 year
Attenuator	Weinschel	33-10-33	AR4010	2024.04.25	2027.04.24	3 year
Attenuator	Weinschel	24-20-34	BP4485	2024.04.25	2027.04.24	3 year
MXA Signal Analyzer	Agilent	N9020A	MY49100060	2025.04.17	2026.04.16	1 year
ESG VETCTOR SIGNAL GENERAROR	Agilent	E4438C	MY45093347	2025.04.17	2026.04.16	1 year
Power Splitter	Mini-Circuits/ USA	ZN2PD-63-S+	SF025101428	2024.04.26	2027.04.25	3 year
Coupler	Mini-Circuits	ZADC-10-63-S +	SF794101410	2024.04.26	2027.04.25	3 year
Directional Coupler	MCLI/USA	CB11-20	0D2L51502	2024.04.26	2027.04.25	3 year
Attenuator	Agilent	8495B	MY42147029	2024.04.26	2027.04.25	3 year
Power Meter	DARE	RPR3006W	15I00041SNO 84	2025.04.17	2026.04.16	1 year
MXG Vector Signal Generator	Agilent	N5182A	MY47070317	2025.04.17	2026.04.16	1 year
Wideband Radio Communication Tester Specifications	R&S	CMW500	148500	2025.05.06	2026.05.05	1 year
temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

## Measurement Software

Item	Manufacturer	Software Name	Software Version	Description
1	MWRFTtest	MTS 8310 2.4GHz/5GHz	2.0	RF Conducted Test
2	Farad	EZ-EMC_RE	AIT-03A	RadiatedTest
3	raditeq	RadiMation	2023.1.3	RadiatedTest



## 2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

ETSI EN 300 328 V2.2.2 (2019-07)		
Clause	Test Item	Results
TRANSMITTER PARAMETERS		
4.3.1.2	RF Output Power	Pass
4.3.1.3	Duty cycle, Tx-Sequence, Tx-gap	Not Applicable (See Note 1/2)
4.3.1.4	Accumulated Transmit Time, Frequency Occupation and Hopping Sequence	Pass
4.3.1.5	Hopping Frequency Separation	Pass
4.3.1.6	Medium Utilization (MU) factor	Not Applicable (See Note 1/2)
4.3.1.7	Adaptivity	Not Applicable (See Note 1)
4.3.1.8	Occupied Channel Bandwidth	Pass
4.3.1.9	Transmitter unwanted emission in the OOB domain	Pass
4.3.1.10	Transmitter unwanted emissions in the spurious domain	Pass
RECEIVER PARAMETERS		
4.3.1.11	Receiver Spurious Emissions	Pass
4.3.1.12	Receiver Blocking	Pass

**Note:**

1. These requirements do not apply for equipment with a maximum declared RF output power of less than 10 dBm EIRP or for equipment when operating in a mode where the RF output power is less than 10 dBm EIRP.
2. These requirements apply to non-adaptive frequency hopping equipment or to adaptive frequency hopping equipment operating in a non-adaptive mode
3. The antenna gain provided by customer is used to calculate the EIRP result. NTEK is not responsible for the accuracy of antenna gain parameter.

## 2.1 TEST FACILITY

Shenzhen NTEK Testing Technology Co., Ltd.

Add. : No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China

FCC Registered No.: 463705 IC Registered No.:9270A

CNAS Registration No.:L5516

## 2.2 MAXIMUM MEASUREMENT UNCERTAINTY

For the test methods, according to ETSI EN 300 328 standard, the measurement uncertainty figures shall be calculated in accordance with ETR 100 028-1[4] and shall correspond to an expansion factor(coverage factor)  $k=1.96$  or  $k=2$  (which provide confidence levels of respectively **95 %** and **95.45 %** in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Maximum measurement uncertainty

No.	Item	Uncertainty
1	Occupied Channel Bandwidth	$\pm 5\%$
2	RF output Power,conducted	$\pm 1.5\text{dB}$
3	Power Spectral Density, conducted	$\pm 3\text{dB}$
4	Unwanted emissions, conducted	$\pm 3\text{dB}$
5	All emissions,radiated	$\pm 6\text{dB}$
6	Temperature	$\pm 3^{\circ}\text{C}$
7	Humidity	$\pm 3\%$
9	Time	$\pm 5\%$

## TRANSMITTER PARAMETERS

### 3. RF OUTPUT POWER

#### 3.1 LIMITS OF RF OUTPUT POWER

Refer to chapter 4.3.1.2.3 of ETSI EN 300 328 V2.2.2 (2019-07)

RF OUTPUT POWER	
Condition	Limit
<input type="checkbox"/> Non-adaptive frequency hopping systems	Equal to or less than the value declared by the supplier. This declared value shall be equal to or less than 20 dBm.
<input checked="" type="checkbox"/> Adaptive frequency hopping systems	equal to or less than 20 dBm.

#### 3.2 TEST PROCEDURE


Refer to chapter 5.4.2.2 of ETSI EN 300 328 V2.2.2 (2019-07)

Measurement	
<input checked="" type="checkbox"/> Conducted measurement	<input type="checkbox"/> Radiated measurement

#### 3.3 DEVIATION FROM TEST STANDARD

No deviation

#### 3.4 TEST SETUP



## 3.5 TEST RESULTS

EUT :	Tablet	Model Name :	TAB KINGKONG MINI
Temperature :	20°C	Relative Humidity :	55 %
Pressure :	1012 hPa	Test Voltage :	DC 3.87V
Test Mode :	BT-GFSK/ $\pi$ /4-DQPSK /8-DPSK		

Test data reference attachment

#### 4. ACCUMULATED TRANSMIT TIME, FREQUENCY OCCUPATION AND HOPPING SEQUENCE

##### 4.1 LIMITS OF ACCUMULATED TRANSMIT TIME, FREQUENCY OCCUPATION AND HOPPING SEQUENCE

Refer to chapter 4.3.1.4.3 of ETSI EN 300 328 V2.2.2 (2019-07)

Accumulated Transmit Time	
Condition	Limit
<input type="checkbox"/> Non-adaptive frequency hopping systems	$\leq 15\text{ ms}$ [15 ms * the minimum number of hopping frequencies (N)]
<input checked="" type="checkbox"/> Adaptive frequency hopping systems	$\leq 400\text{ ms}$ in [400 ms * the minimum number of hopping frequencies (N)]
MINIMUM FREQUENCY OCCUPATION TIME	
Condition	Limit
<input type="checkbox"/> Non-adaptive frequency hopping systems	Each hopping frequency of the hopping sequence shall be occupied at least once within a period not exceeding four times the product of the dwell time and the number of hopping frequencies in use.
<input checked="" type="checkbox"/> Adaptive frequency hopping systems	
HOPPING SEQUENCE (S)	
Condition	Limit
<input type="checkbox"/> Non-adaptive frequency hopping systems	$\geq 15$ hopping frequencies or 15/minimum
<input checked="" type="checkbox"/> Adaptive frequency hopping systems	Operating over a minimum of 70% of the Operating in the band 2.4 GHz to 2.4835 GHz
	$\geq 15$ hopping frequencies or 15/minimum

##### 4.2 TEST PROCEDURE

Refer to chapter 5.4.4 of ETSI EN 300 328 V2.2.2 (2019-07)

Measurement	
<input checked="" type="checkbox"/> Conducted measurement	<input type="checkbox"/> Radiated measurement

##### 4.3 DEVIATION FROM TEST STANDARD

No deviation

#### 4.4 TEST SETUP



The measurements only were performed at normal test conditions. The equipment was configured to operate at its maximum Dwell time and maximum Duty Cycle. The measurement was performed on a minimum of 2 hopping frequencies chosen arbitrary from the actual hopping sequence. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator. Controlling software (Button Function) has been activated to set the EUT on specific status.

#### 4.5 TEST RESULTS

EUT :	Tablet	Model Name :	TAB KINGKONG MINI
Temperature :	26°C	Relative Humidity	60 %
Pressure :	1012 hPa	Test Voltage :	DC 3.87V
Test Mode :	BT-GFSK/ $\pi$ /4-DQPSK /8-DPSK-Hopping Mode		

Test data reference attachment

## 5. OCCUPIED CHANNEL BANDWIDTH

### 5.1 LIMITS OF OCCUPIED CHANNEL BANDWIDTH

Refer to chapter 4.3.1.8.3 of ETSI EN 300 328 V2.2.2 (2019-07)

OCCUPIED CHANNEL BANDWIDTH		
Condition		Limit
All types of equipment		Shall fall completely within the band 2400 to 2483.5 MHz
Additional requirement	For non-adaptive using wide band modulations other than FHSS system and EIRP >10 dBm	Less than 20 MHz
	For non-adaptive frequency hopping system and EIRP >10 dBm	Less than 5 MHz

### 5.2 TEST PROCEDURE

Refer to chapter 5.4.7.2 of ETSI EN 300 328 V2.2.2 (2019-07)

Measurement	
<input checked="" type="checkbox"/> Conducted measurement	<input type="checkbox"/> Radiated measurement

The setting of the Spectrum Analyzer

Center Frequency	The centre frequency of the channel under test
Frequency Span	2 × Nominal Channel Bandwidth
Detector	RMS
RBW	~ 1 % of the span without going below 1 %
VBW	3 × RBW
Trace	Max hold
Sweep time	1s

### 5.3 DEVIATION FROM TEST STANDARD

No deviation

### 5.4 TEST SETUP



These measurements only were performed at normal test conditions. The measurement shall be performed only on the lowest and the highest frequency within the ststed frequency range. Using software to force the EUT to hop or transmit on a single Hopping frequency. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator. Controlling software (Button Function) has been activated to set the EUT on specific status.

### 5.5 TEST RESULTS

EUT :	Tablet	Model Name :	TAB KINGKONG MINI
Temperature :	26°C	Relative Humidity :	60 %
Pressure :	1012 hPa	Test Voltage :	DC 3.87V
Test Mode :	BT-GFSK/ $\pi$ /4-DQPSK /8-DPSK-(CH00/CH78)		

Test data reference attachment



## 6. TRANSMITTER UNWANTED EMISSIONS IN THE OUT-OF-BAND DOMAIN

### 6.1 LIMITS OF TRANSMITTER UNWANTED EMISSIONS IN THE OUT-OF-BAND DOMAIN

Refer to chapter 4.3.1.9.3 of ETSI EN 300 328 V2.2.2 (2019-07)

TRANSMITTER UNWANTED EMISSIONS IN THE OUT-OF-BAND DOMAIN	
Condition	Limit
Under all test conditions	The transmitter unwanted emissions in the out-of-band domain but outside the allocated band, shall not exceed the values provided by the mask in below figure.




Figure 1: Transmit mask

### 6.2 TEST PROCEDURE

Refer to chapter 5.4.8.2 of ETSI EN 300 328 V2.2.2 (2019-07)

Measurement	
<input checked="" type="checkbox"/> Conducted measurement	<input type="checkbox"/> Radiated measurement


The setting of the Spectrum Analyzer

Span	0Hz
Filter Mode	Channel Filter
Trace Mode	Clear/Write
Trigger Mode	Video Trigger
Detector	RMS
Sweep Point / Sweep Mode	5000 / Continuous
RBW / VBW	1MHz / 3MHz

### 6.3 DEVIATION FROM TEST STANDARD

No deviation

### 6.4 TEST SETUP



According to the ETSI EN 300328 V2.2.2 clause 5.4.8.1: These measurements shall only be performed at normal test conditions. For equipment using FHSS modulation, the measurements shall be performed during normal operation (hopping).

For equipment using wide band modulations other than FHSS, the measurement shall be performed at the lowest and the highest channel on which the equipment can operate. These operating channels shall be recorded.

The equipment shall be configured to operate under its worst case situation with respect to output power.

If the equipment can operate with different Nominal Channel Bandwidths (e.g. 20 MHz and 40 MHz), then each channel bandwidth shall be tested separately.

### 6.5 TEST RESULTS

EUT :	Tablet	Model Name :	TAB KINGKONG MINI
Temperature :	26°C	Relative Humidity :	60 %
Pressure :	1012 hPa	Test Voltage :	DC 3.87V
Test Mode :	BT-GFSK/ $\pi$ /4-DQPSK /8-DPSK-(CH78)		

Test data reference attachment

## 7. HOPPING FREQUENCY SEPARATION

### 7.1 LIMITS OF HOPPING FREQUENCY SEPARATION

Refer to chapter 4.3.1.5.3 of ETSI EN 300 328 V2.2.2 (2019-07)

HOPPING FREQUENCY SEPARATION	
Condition	Limit
<input type="checkbox"/> Non-adaptive frequency hopping systems	The minimum Hopping Frequency Separation shall be equal to or greater than occupied channel bandwidth of a single hop, with a minimum separation of 100 kHz.
<input checked="" type="checkbox"/> Adaptive frequency hopping systems	The minimum Hopping Frequency Separation shall be 100 kHz.

### 7.2 TEST PROCEDURE

Refer to chapter 5.4.5.2 of ETSI EN 300 328 V2.2.2 (2019-07)

Measurement	
<input checked="" type="checkbox"/> Conducted measurement	<input type="checkbox"/> Radiated measurement

The setting of the Spectrum Analyzer

Center Frequency	Centre of the two adjacent hopping frequencies
Frequency Span	Sufficient to see the complete power envelope of both hopping frequencies
Detector	Max Peak
RBW	~ 1 % of the span
VBW	3 × RBW
Trace	Max hold
Sweep Time	Auto

### 7.3 DEVIATION FROM TEST STANDARD

No deviation

## 7.4 TEST SETUP



The measurements were performed at normal test conditions. The measurement was performed on 2 adjacent hopping frequencies. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator. Controlling software (Button Function) has been activated to set the EUT on specific status.

## 7.5 TEST RESULTS

EUT :	Tablet	Model Name :	TAB KINGKONG MINI
Temperature :	26°C	Relative Humidity :	60 %
Pressure :	1012 hPa	Test Voltage :	DC 3.87V
Test Mode :	BT-GFSK/ $\pi$ /4-DQPSK /8-DPSK-(CH00/CH39/CH78)		

## Test data reference attachment

Note: 1.The limitation is from OCB of a single hop and this value must greater and equal to 100kHz.  
2.The device will never “hop” to its neighbour channel, therefore the “effective” channel separation becomes 2x the “normal” channel separation.

## 8. TRANSMITTER UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN

### 8.1 LIMITS OF TRANSMITTER TRANSMITTER UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN

Refer to chapter 4.3.1.10.3 of ETSI EN 300 328 V2.2.2 (2019-07)

TRANSMITTER UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN		
Frequency Range	Maximum Power Limit (E.R.P.( $\leq 1$ GHz) E.I.R.P.( $> 1$ GHz))	Bandwidth
30 MHz to 47 MHz	-36dBm	100 kHz
47 MHz to 74 MHz	-54dBm	100 kHz
74 MHz to 87.5 MHz	-36dBm	100 kHz
87.5 MHz to 118 MHz	-54dBm	100 kHz
118 MHz to 174 MHz	-36dBm	100 kHz
174 MHz to 230 MHz	-54dBm	100 kHz
230 MHz to 470 MHz	-36dBm	100 kHz
470 MHz to 694 MHz	-54dBm	100 kHz
694 MHz to 1 GHz	-36dBm	100 kHz
1 GHz ~ 12.75 GHz	-30dBm	1 MHz

### 8.2 TEST PROCEDURE

Refer to chapter 5.4.9.2 of ETSI EN 300 328 V2.2.2 (2019-07)

Measurement	
<input checked="" type="checkbox"/> Conducted measurement	<input checked="" type="checkbox"/> Radiated measurement

The setting of the Spectrum Analyzer


RBW	100K(<1GHz) / 1M(>1GHz)
VBW	300K(<1GHz) / 3M(>1GHz)

### 8.3 DEVIATION FROM TEST STANDARD

No deviation

## 8.4 TEST SETUP

Radiated measurement:



Conducted measurement:



1. For the actual test configuration, please refer to the related Item in this test report (Photographs of the Test Configuration ).
2. The measurements were performed when normal hopping was disabled. In this case measurements were performed when operating at the lowest and the highest hopping frequency.
3. The equipment was configured to operate under its worst case situation with respect to output power.
4. The test setup has been constructed as the normal use condition. Controlling software (Button Function) has been activated to set the EUT on specific status.

## 8.5 TEST RESULTS (Radiated measurement)

### BELOW 1 GHz WORST- CASE DATA (30 MHz ~ 1GHz)

EUT :	Tablet	Model Name :	TAB KINGKONG MINI
Temperature :	24 °C	Relative Humidity	54%
Pressure :	1010 hPa	Test Power :	DC 3.87V
Test Mode :	BT-GFSK (CH00)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
V	43.797	-63.96	10.77	-53.19	-36	-17.19	peak
V	96.481	-76.64	11.26	-65.38	-54	-11.38	peak
V	225.747	-75.3	11.22	-64.08	-54	-10.08	peak
V	321.102	-67	11.19	-55.81	-36	-19.81	peak
V	547.97	-77.91	9.53	-68.38	-54	-14.38	peak
H	43.131	-63.35	10.45	-52.90	-36	-16.90	peak
H	112.415	-75.75	10.20	-65.55	-54	-11.55	peak
H	214.445	-76.04	10.83	-65.21	-54	-11.21	peak
H	449.645	-62.88	11.11	-51.77	-36	-15.77	peak
H	568.104	-76.62	11.03	-65.59	-54	-11.59	peak

#### Remark:

1. Emission Level= Meter Reading+ Factor, Margin= Limit- Emission Level.
2. All the modes had been tested, but only the worst data recorded in the report.



### ABOVE 1 GHz WORST- CASE DATA (1GHz ~ 12.75GHz)

EUT :	Tablet	Model Name :	TAB KINGKONG MINI
Temperature :	24 °C	Relative Humidity	54%
Pressure :	1010 hPa	Test Power :	DC 3.87V
Test Mode :	GFSK (CH00/CH39/CH78)		

Polar (H/V)	Frequency (MHz)	Meter Reading (dBm)	Factor (dB)	Emission Level (dBm)	Limits (dBm)	Margin (dB)	Remark
<b>operation frequency:2402</b>							
V	2228.972	-50.39	10.22	-40.17	-30	-10.17	peak
V	5785.204	-46.78	9.68	-37.10	-30	-7.10	peak
V	2907.875	-48.21	10.95	-37.26	-30	-7.26	peak
V	5876.252	-45.18	9.85	-35.33	-30	-5.33	peak
H	2868.806	-47.03	10.50	-36.53	-30	-6.53	peak
H	5019.315	-50.1	11.22	-38.88	-30	-8.88	peak
H	2058.378	-47.24	10.13	-37.11	-30	-7.11	peak
H	3681.81	-51.37	10.38	-40.99	-30	-10.99	peak
<b>operation frequency:2441</b>							
V	2300.606	-50.75	10.17	-40.58	-30	-10.58	peak
V	3563.962	-46.05	10.22	-35.83	-30	-5.83	peak
V	2524.902	-49.7	10.42	-39.28	-30	-9.28	peak
V	4912.356	-46.68	10.79	-35.89	-30	-5.89	peak
H	2269.876	-48.55	9.82	-38.73	-30	-8.73	peak
H	4638.083	-49.51	9.57	-39.94	-30	-9.94	peak
H	2752.325	-49.88	9.66	-40.22	-30	-10.22	peak
H	4666.327	-51.21	11.33	-39.88	-30	-9.88	peak
<b>operation frequency:2480</b>							
V	2997.728	-48.02	10.13	-37.89	-30	-7.89	peak
V	3042.965	-50.27	9.68	-40.59	-30	-10.59	peak
V	2158.777	-49.26	10.78	-38.48	-30	-8.48	peak
V	5525.294	-51.06	10.82	-40.24	-30	-10.24	peak
H	2895.376	-46.6	11.38	-35.22	-30	-5.22	peak
H	5670.684	-47.78	10.36	-37.42	-30	-7.42	peak
H	2270.801	-49.27	10.60	-38.67	-30	-8.67	peak
H	5023.583	-47.02	10.51	-36.51	-30	-6.51	peak
<b>Remark:</b> 1. Emission Level= Meter Reading+ Factor, Margin= Limit- Emission Level. 2. All the modes had been tested, but only the worst data recorded in the report.							

### 8.6 TEST RESULTS (Conducted measurement)

Test data reference attachment



## 9. RECEIVER SPURIOUS EMISSIONS

### 9.1 LIMITS OF RECEIVER SPURIOUS RADIATION

Refer to chapter 4.3.1.11.3 of ETSI EN 300 328 V2.2.2 (2019-07)

RECEIVER SPURIOUS EMISSIONS		
Frequency Range	Maximum Power Limit (E.R.P.( $\leq 1$ GHz) E.I.R.P.( $> 1$ GHz))	Measurement Bandwidth
30 MHz ~ 1 GHz	-57dBm	100KHz
1 GHz ~ 12.75 GHz	-47dBm	1MHz

### 9.2 TEST PROCEDURE

Refer to chapter 5.4.10.2 of ETSI EN 300 328 V2.2.2 (2019-07)

Measurement	
<input checked="" type="checkbox"/> Conducted measurement	<input checked="" type="checkbox"/> Radiated measurement

The setting of the Spectrum Analyzer


RBW	100K(<1GHz) / 1M(>1GHz)
VBW	300K(<1GHz) / 3M(>1GHz)

### 9.3 DEVIATION FROM TEST STANDARD


No deviation

## 9.4 TEST SETUP

Radiated measurement:



Conducted measurement:



1. For the actual test configuration, please refer to the related Item in this test report (Photographs of the Test Configuration ).
2. Testing was performed when the equipment was in a receive-only mode.
3. The measurements were performed when normal hopping was disabled. In this case measurements were performed when operating at the lowest and the highest hopping frequency.
4. The test setup has been constructed as the normal use condition. Controlling software (Button Function) has been activated to set the EUT on specific status.

## 9.5 TEST RESULTS (Radiated measurement)

### RX BELOW 1 GHz WORST- CASE DATA (30 MHz ~ 1GHz)

EUT :	Tablet	Model Name :	TAB KINGKONG MINI
Temperature :	24 °C	Relative Humidity	54%
Pressure :	1010 hPa	Test Power :	DC 3.87V
Test Mode :	GFSK(CH00)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
V	31.701	-79.39	12.25	-67.14	-57	-10.14	peak
V	99.344	-83.06	16.13	-66.93	-57	-9.93	peak
V	202.052	-82.99	14.05	-68.94	-57	-11.94	peak
V	261.296	-84.3	17.01	-67.29	-57	-10.29	peak
V	595.939	-83.37	15.51	-67.86	-57	-10.86	peak
H	41.032	-82.86	14.62	-68.24	-57	-11.24	peak
H	94.43	-82.46	17.87	-64.59	-57	-7.59	peak
H	192.809	-82.91	16.70	-66.21	-57	-9.21	peak
H	395.486	-83.82	15.79	-68.03	-57	-11.03	peak
H	627.334	-81.35	17.54	-63.81	-57	-6.81	peak

#### Remark:

1. Emission Level= Meter Reading+ Factor, Margin= Limit- Emission Level.
2. All the modes had been tested, but only the worst data recorded in the report.

## RX ABOVE 1 GHz WORST- CASE DATA (1GHz ~ 12.75GHz)

EUT :	Tablet	Model Name :	TAB KINGKONG MINI
Temperature :	24 °C	Relative Humidity	54%
Pressure :	1010 hPa	Test Power :	DC 3.87V
Test Mode :	GFSK (CH00)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
V	2614.379	-68.52	10.46	-58.06	-47	-11.06	peak
V	3516.797	-67.52	10.21	-57.31	-47	-10.31	peak
V	2793.078	-66.2	10.57	-55.63	-47	-8.63	peak
V	3858.227	-67.12	16.88	-50.24	-47	-3.24	peak
H	2538.157	-66.7	10.29	-56.41	-47	-9.41	peak
H	4698.546	-68.38	11.29	-57.09	-47	-10.09	peak
H	2014.83	-69.36	6.79	-62.57	-47	-15.57	peak
H	3330.332	-67.24	15.06	-52.18	-47	-5.18	peak

1. Emission Level= Meter Reading+ Factor, Margin= Limit- Emission Level.
2. All the modes had been tested, but only the worst data recorded in the report.

## 9.6 TEST RESULTS (Conducted measurement)

Test data reference attachment

## 10. RECEIVER BLOCKING

### 10.1 PERFORMANCE CRITERIA

The minimum performance criterion shall be a PER less than or equal to 10 %. The manufacturer may declare alternative performance criteria as long as that is appropriate for the intended use of the equipment (see clause 5.4.1.t)).

### 10.2 LIMITS OF RECEIVER BLOCKING

While maintaining the minimum performance criteria as defined in clause 4.3.1.12.3, the blocking levels at specified frequency offsets shall be equal to or greater than the limits defined for the applicable receiver category provided in table 6, table 7 or table 8.

☐ **Table 6: Receiver Blocking parameters for Receiver Category 1 equipment**

Wanted signal mean power from companion device (dBm) (see notes 1 and 4)	Blocking signal Frequency (MHz)	Blocking signal power (dBm) (see note 4)	Type of blocking signal
(-133 dBm + 10 × log <sub>10</sub> (OCBW)) or -68 dBm whichever is less (see note 2)	2 380 2 504	-34	CW
(-139 dBm + 10 × log <sub>10</sub> (OCBW)) or -74 dBm whichever is less (see note 3)	2 300 2 330 2 360 2524 2584 2674		

NOTE 1: OCBW is in Hz.

NOTE 2: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to  $P_{min} + 26$  dB where  $P_{min}$  is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal.

NOTE 3: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to  $P_{min} + 20$  dB where  $P_{min}$  is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal.

NOTE 4: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density (PFD) in front of the UUT antenna with the UUT being configured/positioned as recorded in clause 5.4.3.2.2.

☒ **Table 7: Receiver Blocking parameters receiver category 2 equipment**

Wanted signal mean power from companion device (dBm) (see notes 1 and 3)	Blocking signal Frequency (MHz)	Blocking signal power (dBm) (see note 3)	Type of blocking signal
(-139 dBm + 10 × log <sub>10</sub> (OCBW) + 10 dB) or (-74 dBm + 10 dB) whichever is less (see note 2)	2 380	-34	CW
	2 504		
	2 300		
	2 584		

NOTE 1: OCBW is in Hz.

NOTE 2: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to  $P_{min} + 26$  dB where  $P_{min}$  is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal.

NOTE 3: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density (PFD) in front of the UUT antenna with the UUT being configured/positioned as recorded in clause 5.4.3.2.2.

☐ **Table 8: Receiver Blocking parameters receiver category 3 equipment**

Wanted signal mean power from companion device (dBm)	Blocking signal Frequency (MHz)	Blocking signal power (dBm) (see note 2)	Type of blocking signal
(-139 dBm + 10 × log <sub>10</sub> (OCBW) + 20 dB) or (-74 dBm + 20 dB) whichever is less (see note 2)	2 380	-34	CW
	2 504		
	2 300		
	2 584		

NOTE 1: OCBW is in Hz.

NOTE 2: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative the test may be performed using a wanted signal up to  $P_{min} + 30$  dB where  $P_{min}$  is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal.

NOTE 3: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density (PFD) in front of the UUT antenna with the UUT being configured/positioned as recorded in clause 5.4.3.2.2.

### 10.3 TEST PROCEDURE


Refer to chapter 5.4.11.2 of ETSI EN 300 328 V2.2.2 (2019-07)

Measurement	
<input checked="" type="checkbox"/> Conducted measurement	<input type="checkbox"/> Radiated measurement

## 10.4 DEVIATION FROM TEST STANDARD

No deviation

## 10.5 TEST SETUP



## 10.6 TEST RESULTS

EUT :	Tablet	Model Name :	TAB KINGKONG MINI
Temperature :	24 °C	Relative Humidity	54%
Pressure :	1010 hPa	Test Power :	DC 3.87V
Test Mode :	GFSK Hopping mode (RX)		

### CH00

#### receiver category 2

Wanted signal mean power from companion device (dBm) (see notes 1 and 3)	Blocking signal Frequency (MHz)	Blocking signal power(dBm) (see note 3)	PER %	PER Limit %
-69.64	2 380	-34	0.84%	≤10
	2 504		0.46%	
	2 300		0.96%	≤10
	2 584		0.59%	

### CH78

#### receiver category 2

Wanted signal mean power from companion device (dBm) (see notes 1 and 3)	Blocking signal Frequency (MHz)	Blocking signal power(dBm) (see note 3)	PER %	PER Limit %
-69.56	2 380	-34	0.15%	≤10
	2 504		0.51%	
	2 300		0.18%	≤10
	2 584		0.05%	

Note: (1) The above results were obtained from laboratory tests.



EUT :	Tablet	Model Name :	TAB KINGKONG MINI
Temperature :	24 °C	Relative Humidity	54%
Pressure :	1010 hPa	Test Power :	DC 3.87V
Test Mode :	$\pi/4$ DQPSK Hopping mode (RX)		

## CH00

## receiver category 2

Wanted signal mean power from companion device (dBm) (see notes 1 and 3)	Blocking signal Frequency (MHz)	Blocking signal power(dBm) (see note 3)	PER %	PER Limit %
-68.25	2 380	-34	0.12%	≤10
	2 504		0.46%	
	2 300		0.00%	≤10
	2 584		0.54%	

## CH78

## receiver category 2

Wanted signal mean power from companion device (dBm) (see notes 1 and 3)	Blocking signal Frequency (MHz)	Blocking signal power(dBm) (see note 3)	PER %	PER Limit %
-68.26	2 380	-34	0.18%	≤10
	2 504		0.85%	
	2 300		0.17%	≤10
	2 584		0.24%	

Note: (1) The above results were obtained from laboratory tests.

EUT :	Tablet	Model Name :	TAB KINGKONG MINI
Temperature :	24 °C	Relative Humidity	54%
Pressure :	1010 hPa	Test Power :	DC 3.87V
Test Mode :	8-DPSK Hopping mode (RX)		

## CH00

## receiver category 2

Wanted signal mean power from companion device (dBm) (see notes 1 and 3)	Blocking signal Frequency (MHz)	Blocking signal power(dBm) (see note 3)	PER %	PER Limit %
-68.22	2 380	-34	0.24%	≤10
	2 504		0.42%	
	2 300		0.31%	≤10
	2 584		0.11%	

## CH78

## receiver category 2



Wanted signal mean power from companion device (dBm) (see notes 1 and 3)	Blocking signal Frequency (MHz)	Blocking signal power(dBm) (see note 3)	PER %	PER Limit %
-68.23	2 380	-34	0.56%	≤10
	2 504		0.17%	
	2 300		0.76%	≤10
	2 584		0.67%	



Note: (1) The above results were obtained from laboratory tests.



## 11. TEST RESULTS



### 11.1 Accumulated Transmit Time



Condition	Mode	Frequency (MHz)	Antenna	Accumulated Transmit Time (ms)	Limit (ms)	Sweep Time (ms)	Burst Number	Verdict
NVNT	1-DH1	2402	Ant1	129.92	400	31600	320	Pass
NVNT	1-DH1	2480	Ant1	129.108	400	31600	318	Pass
NVNT	1-DH3	2402	Ant1	250.962	400	31600	151	Pass
NVNT	1-DH3	2480	Ant1	237.666	400	31600	143	Pass
NVNT	1-DH5	2402	Ant1	287.991	400	31600	99	Pass
NVNT	1-DH5	2480	Ant1	302.64	400	31600	104	Pass
NVNT	2-DH1	2402	Ant1	126.166	400	31600	317	Pass
NVNT	2-DH1	2480	Ant1	126.166	400	31600	317	Pass
NVNT	2-DH3	2402	Ant1	262.509	400	31600	159	Pass
NVNT	2-DH3	2480	Ant1	254.254	400	31600	154	Pass
NVNT	2-DH5	2402	Ant1	292.698	400	31600	101	Pass
NVNT	2-DH5	2480	Ant1	275.31	400	31600	95	Pass
NVNT	3-DH1	2402	Ant1	126.324	400	31600	319	Pass
NVNT	3-DH1	2480	Ant1	126.643	400	31600	319	Pass
NVNT	3-DH3	2402	Ant1	265.167	400	31600	161	Pass
NVNT	3-DH3	2480	Ant1	268.461	400	31600	163	Pass
NVNT	3-DH5	2402	Ant1	327.361	400	31600	113	Pass
NVNT	3-DH5	2480	Ant1	269.514	400	31600	93	Pass


































## 11.2 Frequency Occupation



Condition	Mode	Frequency (MHz)	Antenna	Burst Number	Limit	Sweep Time (ms)	Verdict
NVNT	1-DH1	2402	Ant1	1	1	128.296	Pass
NVNT	1-DH1	2480	Ant1	1	1	128.296	Pass
NVNT	1-DH3	2402	Ant1	2	1	525.192	Pass
NVNT	1-DH3	2480	Ant1	3	1	525.192	Pass
NVNT	1-DH5	2402	Ant1	4	1	919.244	Pass
NVNT	1-DH5	2480	Ant1	1	1	919.56	Pass
NVNT	2-DH1	2402	Ant1	2	1	125.768	Pass
NVNT	2-DH1	2480	Ant1	1	1	125.768	Pass
NVNT	2-DH3	2402	Ant1	3	1	521.716	Pass
NVNT	2-DH3	2480	Ant1	2	1	521.716	Pass
NVNT	2-DH5	2402	Ant1	1	1	915.768	Pass
NVNT	2-DH5	2480	Ant1	5	1	915.768	Pass
NVNT	3-DH1	2402	Ant1	1	1	125.136	Pass
NVNT	3-DH1	2480	Ant1	2	1	125.452	Pass
NVNT	3-DH3	2402	Ant1	1	1	520.452	Pass
NVNT	3-DH3	2480	Ant1	5	1	520.452	Pass
NVNT	3-DH5	2402	Ant1	2	1	915.452	Pass
NVNT	3-DH5	2480	Ant1	3	1	915.768	Pass




































### 11.3 Dwell Time One Burst



Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)
NVNT	1-DH1	2402	Ant1	0.406
NVNT	1-DH1	2480	Ant1	0.406
NVNT	1-DH3	2402	Ant1	1.662
NVNT	1-DH3	2480	Ant1	1.662
NVNT	1-DH5	2402	Ant1	2.909
NVNT	1-DH5	2480	Ant1	2.91
NVNT	2-DH1	2402	Ant1	0.398
NVNT	2-DH1	2480	Ant1	0.398
NVNT	2-DH3	2402	Ant1	1.651
NVNT	2-DH3	2480	Ant1	1.651
NVNT	2-DH5	2402	Ant1	2.898
NVNT	2-DH5	2480	Ant1	2.898
NVNT	3-DH1	2402	Ant1	0.396
NVNT	3-DH1	2480	Ant1	0.397
NVNT	3-DH3	2402	Ant1	1.647
NVNT	3-DH3	2480	Ant1	1.647
NVNT	3-DH5	2402	Ant1	2.897
NVNT	3-DH5	2480	Ant1	2.898




































#### 11.4 RF Output Power



Condition	Mode	Frequency (MHz)	Antenna	Max Burst RMS Power (dBm)	Burst Number	Max EIRP (dBm)	Limit (dBm)	Verdict
NVNT	1-DH5	hopping	Ant1	7.03	27	5.63	20	Pass
NVNT	2-DH5	hopping	Ant1	5.18	27	3.78	20	Pass
NVNT	3-DH5	hopping	Ant1	4.87	28	3.47	20	Pass
NVLT	1-DH5	hopping	Ant1	6.35	28	4.95	20	Pass
NVLT	2-DH5	hopping	Ant1	4.59	27	3.19	20	Pass
NVLT	3-DH5	hopping	Ant1	4.3	27	2.9	20	Pass
NVHT	1-DH5	hopping	Ant1	6.32	28	4.92	20	Pass
NVHT	2-DH5	hopping	Ant1	4.49	27	3.09	20	Pass
NVHT	3-DH5	hopping	Ant1	4.1	27	2.7	20	Pass











### 11.5 Hopping Frequency Separation

Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH5	Ant1	2402.009	2403.011	1.002	0.1	Pass
NVNT	1-DH5	Ant1	2441.015	2442.011	0.996	0.1	Pass
NVNT	1-DH5	Ant1	2479.015	2480.01	0.995	0.1	Pass
NVNT	2-DH5	Ant1	2402.026	2403.03	1.004	0.1	Pass
NVNT	2-DH5	Ant1	2441.024	2442.02	0.996	0.1	Pass
NVNT	2-DH5	Ant1	2479.024	2480.026	1.002	0.1	Pass
NVNT	3-DH5	Ant1	2401.962	2403.011	1.049	0.1	Pass
NVNT	3-DH5	Ant1	2440.911	2441.961	1.05	0.1	Pass
NVNT	3-DH5	Ant1	2478.991	2480.02	1.029	0.1	Pass


















### 11.6 Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	Center Frequency (MHz)	OBW (MHz)	Lower Edge (MHz)	Upper Edge (MHz)	Limit OBW (MHz)	Verdict
NVNT	1-DH5	2402	Ant1	2401.998	0.862	2401.567	2402.428	2400 - 2483.5MHz	Pass
NVNT	1-DH5	2480	Ant1	2479.999	0.88	2479.559	2480.439	2400 - 2483.5MHz	Pass
NVNT	2-DH5	2402	Ant1	2401.999	1.189	2401.404	2402.593	2400 - 2483.5MHz	Pass
NVNT	2-DH5	2480	Ant1	2479.998	1.186	2479.405	2480.591	2400 - 2483.5MHz	Pass
NVNT	3-DH5	2402	Ant1	2401.998	1.196	2401.4	2402.596	2400 - 2483.5MHz	Pass
NVNT	3-DH5	2480	Ant1	2479.997	1.193	2479.401	2480.594	2400 - 2483.5MHz	Pass






## OBW NVNT 3-DH5 2402MHz Ant1

Spectrum

Ref Level 20.00 dBm Offset 2.38 dB RBW 30 kHz  
Att 35 dB SWT 1 s VBW 100 kHz Mode Auto Sweep  
SGL Count 30/30

1Rm Max



Marker


Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4014 GHz	-17.20 dBm		
T1		1	2.40139966 GHz	-17.19 dBm	Occ Bw	1.196080392 MHz
T2		1	2.40259574 GHz	-15.24 dBm		

## OBW NVNT 3-DH5 2480MHz Ant1

Spectrum

Ref Level 20.00 dBm Offset 2.42 dB RBW 30 kHz  
Att 35 dB SWT 1 s VBW 100 kHz Mode Auto Sweep  
SGL Count 30/30

1Rm Max



Marker


Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.480594 GHz	-17.14 dBm		
T1		1	2.47940086 GHz	-18.26 dBm	Occ Bw	1.193080692 MHz
T2		1	2.480593941 GHz	-17.14 dBm		

### 11.7 Transmitter unwanted emissions in the out-of-band domain


Condition	Mode	Frequency (MHz)	Antenna	OOB Frequency (MHz)	Level (dBm/MHz)	Limit (dBm/MHz)	Verdict
NVNT	1-DH5	Hopping	Ant1	2399.5	-46.75	-10	Pass
NVNT	1-DH5	Hopping	Ant1	2398.5	-46.3	-20	Pass
NVNT	1-DH5	Hopping	Ant1	2484	-46.05	-10	Pass
NVNT	1-DH5	Hopping	Ant1	2485	-46.07	-20	Pass
NVNT	1-DH5	Hopping	Ant1	2399.5	-46.7	-10	Pass
NVNT	1-DH5	Hopping	Ant1	2398.5	-46.25	-20	Pass
NVNT	1-DH5	Hopping	Ant1	2484	-46.02	-10	Pass
NVNT	1-DH5	Hopping	Ant1	2485	-46.02	-20	Pass
NVNT	2-DH5	Hopping	Ant1	2399.5	-46.34	-10	Pass
NVNT	2-DH5	Hopping	Ant1	2399.311	-46.18	-10	Pass
NVNT	2-DH5	Hopping	Ant1	2398.311	-46.2	-20	Pass
NVNT	2-DH5	Hopping	Ant1	2398.122	-46.23	-20	Pass
NVNT	2-DH5	Hopping	Ant1	2484	-45.99	-10	Pass
NVNT	2-DH5	Hopping	Ant1	2485	-45.98	-20	Pass
NVNT	2-DH5	Hopping	Ant1	2399.5	-46.59	-10	Pass
NVNT	2-DH5	Hopping	Ant1	2398.5	-46.17	-20	Pass
NVNT	2-DH5	Hopping	Ant1	2484	-45.92	-10	Pass
NVNT	2-DH5	Hopping	Ant1	2484.186	-45.95	-10	Pass
NVNT	2-DH5	Hopping	Ant1	2485.186	-45.95	-20	Pass
NVNT	2-DH5	Hopping	Ant1	2485.372	-45.93	-20	Pass
NVNT	3-DH5	Hopping	Ant1	2399.5	-46.36	-10	Pass
NVNT	3-DH5	Hopping	Ant1	2399.304	-46.24	-10	Pass
NVNT	3-DH5	Hopping	Ant1	2398.304	-46.3	-20	Pass
NVNT	3-DH5	Hopping	Ant1	2398.108	-46.3	-20	Pass
NVNT	3-DH5	Hopping	Ant1	2484	-38.45	-10	Pass
NVNT	3-DH5	Hopping	Ant1	2485	-46.07	-20	Pass
NVNT	3-DH5	Hopping	Ant1	2399.5	-46.45	-10	Pass
NVNT	3-DH5	Hopping	Ant1	2398.5	-46.19	-20	Pass
NVNT	3-DH5	Hopping	Ant1	2484	-45.96	-10	Pass
NVNT	3-DH5	Hopping	Ant1	2484.193	-45.95	-10	Pass
NVNT	3-DH5	Hopping	Ant1	2485.193	-45.96	-20	Pass
NVNT	3-DH5	Hopping	Ant1	2485.386	-45.95	-20	Pass

Test Graphs


Tx. Emissions OOB NVNT 1-DH5 2402MHz Ant1




Tx. Emissions OOB NVNT 1-DH5 2480MHz Ant1



Tx. Emissions OOB NVNT 2-DH5 2402MHz Ant1




Tx. Emissions OOB NVNT 2-DH5 2480MHz Ant1






Tx. Emissions OOB NVNT 3-DH5 2402MHz Ant1



Tx. Emissions OOB NVNT 3-DH5 2480MHz Ant1



### 11.8 Transmitter unwanted emissions in the spurious domain

Condition	Mode	Frequency (MHz)	Antenna	Range (MHz)	Spur Freq (MHz)	Peak (dBm)	RMS (dBm)	Limit (dBm)	Verdict
NVNT	1-DH5	2402	Ant1	30 -47	31.35	-80.84	NA	-36	Pass
NVNT	1-DH5	2402	Ant1	47 -74	61.80	-80.24	NA	-54	Pass
NVNT	1-DH5	2402	Ant1	74 -87.5	86.45	-80.35	NA	-36	Pass
NVNT	1-DH5	2402	Ant1	87.5 -118	91.55	-80.16	NA	-54	Pass
NVNT	1-DH5	2402	Ant1	118 -174	137.20	-79.10	NA	-36	Pass
NVNT	1-DH5	2402	Ant1	174 -230	212.80	-78.75	NA	-54	Pass
NVNT	1-DH5	2402	Ant1	230 -470	393.80	-78.36	NA	-36	Pass
NVNT	1-DH5	2402	Ant1	470 -694	599.05	-78.11	NA	-54	Pass
NVNT	1-DH5	2402	Ant1	694 -1000	759.30	-75.90	NA	-36	Pass
NVNT	1-DH5	2402	Ant1	1000 -2398	2395.50	-44.16	NA	-30	Pass
NVNT	1-DH5	2402	Ant1	2485.5 -12750	6914.50	-50.21	NA	-30	Pass
NVNT	1-DH5	2441	Ant1	30 -47	30.75	-80.44	NA	-36	Pass
NVNT	1-DH5	2441	Ant1	47 -74	61.55	-80.63	NA	-54	Pass
NVNT	1-DH5	2441	Ant1	74 -87.5	87.35	-79.64	NA	-36	Pass
NVNT	1-DH5	2441	Ant1	87.5 -118	115.10	-79.30	NA	-54	Pass
NVNT	1-DH5	2441	Ant1	118 -174	163.75	-79.68	NA	-36	Pass
NVNT	1-DH5	2441	Ant1	174 -230	222.65	-78.36	NA	-54	Pass
NVNT	1-DH5	2441	Ant1	230 -470	354.75	-78.29	NA	-36	Pass
NVNT	1-DH5	2441	Ant1	470 -694	578.50	-78.35	NA	-54	Pass
NVNT	1-DH5	2441	Ant1	694 -1000	963.50	-77.03	NA	-36	Pass
NVNT	1-DH5	2441	Ant1	1000 -2398	2376.50	-55.22	NA	-30	Pass
NVNT	1-DH5	2441	Ant1	2485.5 -12750	6950.50	-50.10	NA	-30	Pass
NVNT	1-DH5	2480	Ant1	30 -47	34.40	-80.22	NA	-36	Pass
NVNT	1-DH5	2480	Ant1	47 -74	68.60	-80.79	NA	-54	Pass
NVNT	1-DH5	2480	Ant1	74 -87.5	80.85	-79.90	NA	-36	Pass
NVNT	1-DH5	2480	Ant1	87.5 -118	104.50	-79.92	NA	-54	Pass
NVNT	1-DH5	2480	Ant1	118 -174	141.95	-78.98	NA	-36	Pass
NVNT	1-DH5	2480	Ant1	174 -230	226.30	-78.14	NA	-54	Pass
NVNT	1-DH5	2480	Ant1	230 -470	332.15	-78.41	NA	-36	Pass
NVNT	1-DH5	2480	Ant1	470 -694	607.05	-77.56	NA	-54	Pass
NVNT	1-DH5	2480	Ant1	694 -1000	951.50	-77.45	NA	-36	Pass
NVNT	1-DH5	2480	Ant1	1000 -2398	2352.00	-55.77	NA	-30	Pass
NVNT	1-DH5	2480	Ant1	2485.5 -12750	2486.50	-43.52	NA	-30	Pass
NVNT	2-DH5	2402	Ant1	30 -47	33.95	-80.24	NA	-36	Pass
NVNT	2-DH5	2402	Ant1	47 -74	48.15	-80.31	NA	-54	Pass
NVNT	2-DH5	2402	Ant1	74 -87.5	83.40	-80.75	NA	-36	Pass
NVNT	2-DH5	2402	Ant1	87.5 -118	107.50	-79.27	NA	-54	Pass
NVNT	2-DH5	2402	Ant1	118 -174	167.35	-79.07	NA	-36	Pass
NVNT	2-DH5	2402	Ant1	174 -230	182.75	-79.18	NA	-54	Pass
NVNT	2-DH5	2402	Ant1	230 -470	368.75	-78.40	NA	-36	Pass
NVNT	2-DH5	2402	Ant1	470 -694	647.00	-77.87	NA	-54	Pass
NVNT	2-DH5	2402	Ant1	694 -1000	769.95	-75.91	NA	-36	Pass
NVNT	2-DH5	2402	Ant1	1000 -2398	2397.00	-42.53	NA	-30	Pass
NVNT	2-DH5	2402	Ant1	2485.5 -12750	6941.50	-50.11	NA	-30	Pass
NVNT	2-DH5	2441	Ant1	30 -47	40.45	-80.48	NA	-36	Pass
NVNT	2-DH5	2441	Ant1	47 -74	57.25	-80.44	NA	-54	Pass
NVNT	2-DH5	2441	Ant1	74 -87.5	85.45	-79.65	NA	-36	Pass
NVNT	2-DH5	2441	Ant1	87.5 -118	100.55	-80.17	NA	-54	Pass
NVNT	2-DH5	2441	Ant1	118 -174	165.85	-77.92	NA	-36	Pass
NVNT	2-DH5	2441	Ant1	174 -230	208.25	-78.88	NA	-54	Pass
NVNT	2-DH5	2441	Ant1	230 -470	363.90	-78.47	NA	-36	Pass
NVNT	2-DH5	2441	Ant1	470 -694	617.70	-77.88	NA	-54	Pass
NVNT	2-DH5	2441	Ant1	694 -1000	768.50	-74.94	NA	-36	Pass
NVNT	2-DH5	2441	Ant1	1000 -2398	2376.50	-55.57	NA	-30	Pass
NVNT	2-DH5	2441	Ant1	2485.5 -12750	6846.00	-48.98	NA	-30	Pass
NVNT	2-DH5	2480	Ant1	30 -47	31.70	-79.50	NA	-36	Pass
NVNT	2-DH5	2480	Ant1	47 -74	73.35	-80.00	NA	-54	Pass
NVNT	2-DH5	2480	Ant1	74 -87.5	78.85	-80.40	NA	-36	Pass


NVNT	2-DH5	2480	Ant1	87.5 -118	94.90	-79.03	NA	-54	Pass
NVNT	2-DH5	2480	Ant1	118 -174	152.60	-79.03	NA	-36	Pass
NVNT	2-DH5	2480	Ant1	174 -230	213.80	-78.68	NA	-54	Pass
NVNT	2-DH5	2480	Ant1	230 -470	318.90	-78.67	NA	-36	Pass
NVNT	2-DH5	2480	Ant1	470 -694	630.85	-78.12	NA	-54	Pass
NVNT	2-DH5	2480	Ant1	694 -1000	768.45	-74.43	NA	-36	Pass
NVNT	2-DH5	2480	Ant1	1000 -2398	2351.50	-55.74	NA	-30	Pass
NVNT	2-DH5	2480	Ant1	2485.5 -12750	2489.00	-46.74	NA	-30	Pass
NVNT	3-DH5	2402	Ant1	30 -47	41.95	-80.79	NA	-36	Pass
NVNT	3-DH5	2402	Ant1	47 -74	48.60	-80.72	NA	-54	Pass
NVNT	3-DH5	2402	Ant1	74 -87.5	79.35	-80.26	NA	-36	Pass
NVNT	3-DH5	2402	Ant1	87.5 -118	107.80	-78.98	NA	-54	Pass
NVNT	3-DH5	2402	Ant1	118 -174	145.70	-79.22	NA	-36	Pass
NVNT	3-DH5	2402	Ant1	174 -230	187.65	-78.30	NA	-54	Pass
NVNT	3-DH5	2402	Ant1	230 -470	373.85	-78.02	NA	-36	Pass
NVNT	3-DH5	2402	Ant1	470 -694	503.60	-77.70	NA	-54	Pass
NVNT	3-DH5	2402	Ant1	694 -1000	933.80	-77.01	NA	-36	Pass
NVNT	3-DH5	2402	Ant1	1000 -2398	2397.50	-42.53	NA	-30	Pass
NVNT	3-DH5	2402	Ant1	2485.5 -12750	6955.50	-50.38	NA	-30	Pass
NVNT	3-DH5	2441	Ant1	30 -47	37.30	-80.34	NA	-36	Pass
NVNT	3-DH5	2441	Ant1	47 -74	47.85	-80.12	NA	-54	Pass
NVNT	3-DH5	2441	Ant1	74 -87.5	76.45	-80.13	NA	-36	Pass
NVNT	3-DH5	2441	Ant1	87.5 -118	93.95	-79.81	NA	-54	Pass
NVNT	3-DH5	2441	Ant1	118 -174	156.35	-79.02	NA	-36	Pass
NVNT	3-DH5	2441	Ant1	174 -230	223.30	-78.72	NA	-54	Pass
NVNT	3-DH5	2441	Ant1	230 -470	414.35	-78.49	NA	-36	Pass
NVNT	3-DH5	2441	Ant1	470 -694	593.95	-77.88	NA	-54	Pass
NVNT	3-DH5	2441	Ant1	694 -1000	769.50	-73.70	NA	-36	Pass
NVNT	3-DH5	2441	Ant1	1000 -2398	2312.50	-55.59	NA	-30	Pass
NVNT	3-DH5	2441	Ant1	2485.5 -12750	6999.50	-50.07	NA	-30	Pass
NVNT	3-DH5	2480	Ant1	30 -47	36.95	-80.57	NA	-36	Pass
NVNT	3-DH5	2480	Ant1	47 -74	72.30	-80.54	NA	-54	Pass
NVNT	3-DH5	2480	Ant1	74 -87.5	77.85	-79.37	NA	-36	Pass
NVNT	3-DH5	2480	Ant1	87.5 -118	104.00	-79.45	NA	-54	Pass
NVNT	3-DH5	2480	Ant1	118 -174	144.05	-79.54	NA	-36	Pass
NVNT	3-DH5	2480	Ant1	174 -230	192.45	-78.67	NA	-54	Pass
NVNT	3-DH5	2480	Ant1	230 -470	420.35	-77.87	NA	-36	Pass
NVNT	3-DH5	2480	Ant1	470 -694	478.00	-78.49	NA	-54	Pass
NVNT	3-DH5	2480	Ant1	694 -1000	771.25	-75.43	NA	-36	Pass
NVNT	3-DH5	2480	Ant1	1000 -2398	2351.50	-55.94	NA	-30	Pass
NVNT	3-DH5	2480	Ant1	2485.5 -12750	2487.50	-45.54	NA	-30	Pass

Test Graphs

Tx. Spurious NVNT 1-DH5 2402MHz Ant1

Frequency: 2402 MHz


Transmitter unwanted emissions in the spurious domain




Tx. Spurious NVNT 1-DH5 2441MHz Ant1

Frequency: 2441 MHz


Transmitter unwanted emissions in the spurious domain




Tx. Spurious NVNT 1-DH5 2480MHz Ant1




Tx. Spurious NVNT 2-DH5 2402MHz Ant1



Tx. Spurious NVNT 2-DH5 2441MHz Ant1




Tx. Spurious NVNT 2-DH5 2480MHz Ant1







Tx. Spurious NVNT 3-DH5 2402MHz Ant1



Tx. Spurious NVNT 3-DH5 2441MHz Ant1








### 11.9 Receiver spurious emissions


Condition	Mode	Frequency (MHz)	Antenna	Range (MHz)	Spur Freq (MHz)	Peak (dBm)	RMS (dBm)	Limit (dBm)	Verdict
NVNT	1-DH5	2402	Ant1	30 -1000	950.7	-78.11	NA	-57	Pass
NVNT	1-DH5	2402	Ant1	1000 -12750	6939.5	-60.00	NA	-47	Pass
NVNT	1-DH5	2441	Ant1	30 -1000	380.15	-78.19	NA	-57	Pass
NVNT	1-DH5	2441	Ant1	1000 -12750	6836.5	-61.09	NA	-47	Pass
NVNT	1-DH5	2480	Ant1	30 -1000	174.95	-77.87	NA	-57	Pass
NVNT	1-DH5	2480	Ant1	1000 -12750	6908	-61.46	NA	-47	Pass
NVNT	2-DH5	2402	Ant1	30 -1000	826.85	-78.61	NA	-57	Pass
NVNT	2-DH5	2402	Ant1	1000 -12750	6989.5	-61.00	NA	-47	Pass
NVNT	2-DH5	2441	Ant1	30 -1000	928.05	-78.10	NA	-57	Pass
NVNT	2-DH5	2441	Ant1	1000 -12750	6921.5	-60.74	NA	-47	Pass
NVNT	2-DH5	2480	Ant1	30 -1000	993.65	-77.28	NA	-57	Pass
NVNT	2-DH5	2480	Ant1	1000 -12750	6937	-61.88	NA	-47	Pass
NVNT	3-DH5	2402	Ant1	30 -1000	951.95	-76.73	NA	-57	Pass
NVNT	3-DH5	2402	Ant1	1000 -12750	6973	-61.12	NA	-47	Pass
NVNT	3-DH5	2441	Ant1	30 -1000	903.15	-77.75	NA	-57	Pass
NVNT	3-DH5	2441	Ant1	1000 -12750	6959.5	-61.32	NA	-47	Pass
NVNT	3-DH5	2480	Ant1	30 -1000	866.45	-78.07	NA	-57	Pass
NVNT	3-DH5	2480	Ant1	1000 -12750	6758	-61.56	NA	-47	Pass

Test Graphs


Rx. Spurious NVNT 1-DH5 2402MHz Ant1




Rx. Spurious NVNT 1-DH5 2441MHz Ant1




Rx. Spurious NVNT 1-DH5 2480MHz Ant1




Rx. Spurious NVNT 2-DH5 2402MHz Ant1




Rx. Spurious NVNT 2-DH5 2441MHz Ant1




Rx. Spurious NVNT 2-DH5 2480MHz Ant1




Rx. Spurious NVNT 3-DH5 2402MHz Ant1





Rx. Spurious NVNT 3-DH5 2441MHz Ant1






## 11.10 Hopping Sequence

Condition	Mode	Antenna	Hopping Number	Limit	Band Allocation (%)	Limit Band Allocation (%)	Verdict
NVNT	1-DH5	Ant1	79	15	95.6	70	Pass
NVNT	2-DH5	Ant1	79	15	96.2	70	Pass
NVNT	3-DH5	Ant1	79	15	96.2	70	Pass








## 12. EUT TEST PHOTO

### SPURIOUS EMISSIONS MEASUREMENT PHOTOS



END OF REPORT