

Stacking Test Report

堆码试验报告

Applicant's Name 委托方名称	Shenzhen Huafurui Technology Co., Ltd. 深圳市骅福瑞科技有限公司
Applicant's Address 委托方地址	Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993 Jiaxian Road, Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, P.R. China 深圳市龙岗区坂田街道象角塘社区稼先路 993 号赣锋科技大厦 1 栋 A 座六层 601-03 单元
Name of Goods 货物名称	手机 CUBOT P80 (内置可充电锂聚合物电池 C35 3.80V 5200mAh 19.76Wh) Mobile phone CUBOT P80 (Containing Rechargeable Li-polymer battery C35 3.80V 5200mAh 19.76Wh)
Testing Laboratory 测试实验室	Shenzhen TCT Testing Technology Co., Ltd. 深圳市通测检测技术有限公司 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China 广东省深圳市宝安区福海街道桥头社区稔山工业区振昌胶粘制品厂 2101、2201
Report No. 报告编号	TCT241121T045
Date of Issue 签发日期	2024. 12. 02
Test Type 检验类别	Testing by delegation 委托测试
Test Conclusion 测试结论: The test results are qualified. 测试结果为合格。	

Tested by 主检人:

Angela Liao 廖婷

Approved by 批准人:

Tomson 冯瑞君

Reviewer by 审核人:

Cherry Huang 黄懿玲

Seal of TCT 报告单位 (盖章):



I、General product information 一般产品信息:

Name of Goods 货物名称	手机 CUBOT P80 (内置可充电锂聚合物电池 C35 3.80V 5200mAh 19.76Wh) Mobile phone CUBOT P80 (Containing Rechargeable Li-polymer battery C35 3.80V 5200mAh 19.76Wh)		
Packaging Container Manufacturer 包装容器生产商	Shenzhen Zhiang Color Printing and Packaging Products Co., Ltd 深圳市志昂彩印包装制品有限公司		
Packaging Container Manufacturer's Address 包装容器生产商地址	Building 301, No.6 Lingwu Industrial Road, Junzibu Community, Guanlan Street, Longhua District, Shenzhen 深圳市龙华区观澜街道君子布社区凌屋工业路 6 号厂房 301		
Packaging Parts Manufacturer 包装件生产商	Shenzhenshi Jiuliyuan electronic technology co., LTD 深圳市玖利源电子技术有限公司		
Packaging Parts Manufacturer's Address 包装件生产商地址	201, Jiuli Yuan Factory, Building A, No.470, Pingshan Jinbi Road, Biling Community, Biling Street, Pingshan District, Shenzhen 深圳市坪山区碧岭街道碧岭社区坪山金碧路 470 号 A 栋玖利源厂 201		
Shape 形状	Prismatic 棱柱形	Trade Mark 商标	----
Packaging dimensions 包装尺寸 (L×W×T)	(48.3×40.0×24.0) cm	Battery number per packaging 每包装件电池数量	30PCS
Net weight of batteries per package 每包装件电池的净重	1.98kg	Gross weight per package 每包装件毛重	18.27kg
Number of stacking layers 堆码层数	13	The required compressive strength of the carton 纸箱所需抗压强度	219.24kgf
Start Testing Date 开始测试日期	2024-11-30	Completing Date 完成日期	2024-12-02

II、Test Standard 检测标准

United Nations "Recommendations on the Transport of Dangerous Goods-Model Regulations" (Rev.23)
6.1.5.6

联合国《关于危险货物运输的建议书-规章范本》(23 修订版) 6.1.5.6

III、TEST ITEM 检测项目

Stacking test 堆码试验

IV、Test Method and Requirement 检测方法和要求

Ambient temperature 环境温度: 23±2°C

Ambient humidity 环境湿度: 50±2%RH;

Paper or fibreboard packagings shall be conditioned for at least 24 hours in an atmosphere having a controlled temperature and relative humidity (r.h.).

纸和纤维板包装应在控制温度和相对湿度的环境下至少放置 24 小时;

Press plate moving speed 压板移动速度: 10mm/min

Pre pressure 预压力: 219.24kgf

The required compressive strength of the carton

$$= \left(\frac{3m}{\text{Height of single packing case (m)}} - 1 \right) * \text{Weight of single package. The load lasts for 24 hours.}$$

纸箱所需抗压强度 = $\left(\frac{3m}{\text{单个包装箱高度 (m)}} - 1 \right) \times \text{单个包装箱重量}$, 负荷持续 24 小时。

Test requirements 试验要求:

1. The samples in the packing case are not damaged or leaked;
包装箱中的样品没有损坏或泄漏;
2. The test sample must not be damaged in a way that may adversely affect the safety of transport, or deform that may reduce its strength or cause unstable stacking of the package.
试验样品不得显出可能对运输安全有不利影响的损坏, 或者可能降低其强度或造成包装件堆码不稳定的变形;
3. In the case of composite or combination packaging, the contents shall not leak out of the inner receptor and inner package.
对复合或组合包装而言, 不得有所装的物质从内贮器和内包装中漏出。

V、TEST APPARATUS 检测仪器

Serial No. 设备编号	Name of Equipment 设备名称	Model 型号	Calibration Date /Due Date 校准日期/到期日
TC-B117	Carton stacking machine 纸箱堆码试验机	GX-6010-M	2024. 09. 18
			2025. 09. 17
TC-B67	Electronic Platform Scale 电子台秤	TCS-150	2024. 06. 27
			2025. 06. 26
TC-B104	Tape measure 卷尺	TH-2103	2024. 02. 03
			2025. 02. 02

VI、TEST RESULT 检测结果

Drop position 样品编号	Test status 测试结果	Conclusion 结论
X1- X3	<p>After the test 测试后:</p> <ol style="list-style-type: none">The samples in the packing case are not damaged or leaked; 包装箱中的样品没有损坏或泄漏;The test sample does not show damage that may adversely affect the safety of transportation, or deformation that may reduce its strength or cause unstable stacking of the package; 试验样品未显出可能对运输安全有不利影响的损坏, 或者可能降低其强度或造成包装件堆码不稳定的变形;In the case of composite or combination packaging, the contents shall not leak out of the inner receptor and inner package. 对复合或组合包装而言,不得有所装的物质从内贮器和内包装中漏出。	Pass 合格

VII、Appendix Photos 附录图片



Important Notice

注意事项

1. The test report is invalid without the official stamp of TCT.
本报告书无 TCT 盖章无效。
2. Nobody is allowed to photocopy or partly photocopy this test report without written permission of TCT.
未经 TCT 书面同意，不得复制或部分地复制本报告书。
3. The test report is invalid without the signatures of Ratifier, Reviewer and Testing engineer.
本报告书无批准人、审核人、及主检人签名无效。
4. The report is invalid when anything of following happens – illegal transfer, reproduce, embezzlement, imposture, modification or tampering in any media form.
私自转让、复制、盗用、冒用、涂改、或以任何媒体形式篡改的报告书无效。
5. Objections to the test report must be submitted to TCT within 15 days.
对报告书若有异议，应于收到报告之日起 15 天内向本公司提出。
6. The test report is valid for the tested samples only.
本报告仅对本次测试样品有效。
7. The Chinese contents in this report are only for reference.
本报告中的中文内容仅供参考。

*****End of Report 报告结束*****